

## Safety Data Sheet dated 19/7/2016, version 1

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Mixture identification:

Trade name: LINTEX BIANCO NEW

Trade code: 110150L

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Solvent - based enamel

Uses advised against:

None Known

#### 1.3. Details of the supplier of the safety data sheet

Company:

Linvea srl

via Benedetto Croce, 2/4

80026 Arpino Casoria (NA)-ITALY

Tel. +39 081 759 09 22

Fax +39 081 759 77 07

Competent person responsible for the safety data sheet:

dalisalessandro@linvea.it

#### 1.4. Emergency telephone number

Centro Antiveleni - A.O.R.N. "A. Cardarelli" - Napoli -  
tel.+39 081 7472870-5453333, Fax +39 081 7472868  
24/24 h

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):

Warning, Flam. Liq. 3, Flammable liquid and vapour.

Danger, Asp. Tox. 1, May be fatal if swallowed and enters airways.

Warning, STOT SE 3, May cause drowsiness or dizziness.

Aquatic Chronic 3, Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Adverse physicochemical, human health and environmental effects:

No other hazards

#### 2.2. Label elements

Symbols:

Danger

Hazard statements:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P240 Ground/bond container and receiving equipment.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P242 Use only non-sparking tools.  
P243 Take precautionary measures against static discharge.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection.  
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor/...  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P312 Call a POISON CENTER/ doctor/if you feel unwell.  
P331 Do NOT induce vomiting.  
P370+P378 In case of fire: Use ... to extinguish.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.  
P403+P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with applicable regulations.

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Other Hazards:

No other hazards

### SECTION 3: Composition/information on ingredients

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification								
15.9 %	Idrocarburi ,C9-C12,n-alcani,isolacaniciclici,aromatici(2-25%)	<table border="1"> <tr> <td>CAS:</td> <td>1174921-79-9</td> </tr> <tr> <td>EC:</td> <td>919-446-0</td> </tr> <tr> <td>REACH No.:</td> <td>01-2119458049-330004</td> </tr> </table>	CAS:	1174921-79-9	EC:	919-446-0	REACH No.:	01-2119458049-330004	2.6/3 Flam. Liq. 3 H226 3.10/1 Asp. Tox. 1 H304 3.8/3 STOT SE 3 H336 4.1/C2 Aquatic Chronic 2 H411 EUH066		
CAS:	1174921-79-9										
EC:	919-446-0										
REACH No.:	01-2119458049-330004										
2.28 %	o-xylene	<table border="1"> <tr> <td>Index number:</td> <td>601-022-00-9</td> </tr> <tr> <td>CAS:</td> <td>1330-20-7</td> </tr> <tr> <td>EC:</td> <td>215-535-7</td> </tr> <tr> <td>REACH No.:</td> <td>01-2119488216-32</td> </tr> </table>	Index number:	601-022-00-9	CAS:	1330-20-7	EC:	215-535-7	REACH No.:	01-2119488216-32	2.6/3 Flam. Liq. 3 H226 3.2/2 Skin Irrit. 2 H315 3.1/4/Dermal Acute Tox. 4 H312 3.1/4/Inhal Acute Tox. 4 H332
Index number:	601-022-00-9										
CAS:	1330-20-7										
EC:	215-535-7										
REACH No.:	01-2119488216-32										
0.8 %	2-methylpropan-1-ol; iso-butanol	<table border="1"> <tr> <td>Index number:</td> <td>603-108-00-1</td> </tr> <tr> <td>CAS:</td> <td>78-83-1</td> </tr> <tr> <td>EC:</td> <td>201-148-0</td> </tr> <tr> <td>REACH No.:</td> <td>01-2119484609-23</td> </tr> </table>	Index number:	603-108-00-1	CAS:	78-83-1	EC:	201-148-0	REACH No.:	01-2119484609-23	2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H335 3.2/2 Skin Irrit. 2 H315 3.3/1 Eye Dam. 1 H318 3.8/3 STOT SE 3 H336
Index number:	603-108-00-1										
CAS:	78-83-1										
EC:	201-148-0										
REACH No.:	01-2119484609-23										
0.5 %	2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime	<table border="1"> <tr> <td>Index number:</td> <td>616-014-00-0</td> </tr> <tr> <td>CAS:</td> <td>96-29-7</td> </tr> <tr> <td>EC:</td> <td>202-496-6</td> </tr> </table>	Index number:	616-014-00-0	CAS:	96-29-7	EC:	202-496-6	3.6/2 Carc. 2 H351 3.3/1 Eye Dam. 1 H318 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317 3.1/4/Dermal Acute Tox. 4 H312		
Index number:	616-014-00-0										
CAS:	96-29-7										
EC:	202-496-6										
		<table border="1"> <tr> <td>CAS:</td> <td>136-52-7</td> </tr> </table>	CAS:	136-52-7	3.10/1 Asp. Tox. 1 H304 4.1/A1 Aquatic Acute 1 H400						
CAS:	136-52-7										

0.119 %	Bis(2-Etilenoato) di cobalto	EC: 205-250-6 REACH No.: 01-2119524678-29	3.3/2 Eye Irrit. 2 H319 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317 3.7/2 Repr. 2 H361 4.1/C1 Aquatic Chronic 1 H410
2 ppm	ethanediol; ethylene glycol	Index number: 603-027-00-1 CAS: 107-21-1 EC: 203-473-3 REACH No.: 01-2119456816-28	3.1/4/Oral Acute Tox. 4 H302
60 ppb	ammonia, anhydrous	Index number: 007-001-00-5 CAS: 7664-41-7 EC: 231-635-3	2.2/2 Flam. Gas 2 H221 2.5 Press. Gas H280 3.2/1B Skin Corr. 1B H314 4.1/A1 Aquatic Acute 1 H400 3.1/3/Inhal Acute Tox. 3 H331

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

In case of skin contact:

Immediately take off all contaminated clothing.

Remove contaminated clothing immediately and dispose off safely.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do NOT induce vomiting.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

None

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media:

Extinguishing media which must not be used for safety reasons:

None in particular.

##### 5.2. Special hazards arising from the substance or mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

##### 5.3. Advice for firefighters

Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6: Accidental release measures

##### 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Remove all sources of ignition.

Remove persons to safety.

See protective measures under point 7 and 8.

##### 6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

- Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up  
Wash with plenty of water.
- 6.4. Reference to other sections  
See also section 8 and 13

## SECTION 7: Handling and storage

- 7.1. Precautions for safe handling  
Avoid contact with skin and eyes, inhalation of vapours and mists.  
Don't use empty container before they have been cleaned.  
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.  
Contaminated clothing should be changed before entering eating areas.  
Do not eat or drink while working.  
See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities  
Always keep in a well ventilated place.  
Store at below 20 °C. Keep away from unguarded flame and heat sources. Avoid direct exposure to sunlight.  
Keep away from unguarded flame, sparks, and heat sources. Avoid direct exposure to sunlight.  
Avoid accumulating electrostatic charge.  
Keep away from food, drink and feed.  
Incompatible materials:  
None in particular.  
Instructions as regards storage premises:  
Cool and adequately ventilated.  
Safety electric system.
- 7.3. Specific end use(s)  
None in particular

## SECTION 8: Exposure controls/personal protection

- 8.1. Control parameters  
Idrocarburi ,C9-C12,n-alcani,isolacani-ciclici,aromatici(2-25%) - CAS: 1174921-79-9  
ACGIH - STE: 100 ppm - Notes: TWA  
o-xylene - CAS: 1330-20-7  
EU - LTE(8h): 221 mg/m<sup>3</sup>, 50 ppm - STE: 442 mg/m<sup>3</sup>, 100 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)  
ACGIH - LTE(8h): 100 ppm - STE: 150 ppm - Notes: A4, BEI - URT and eye irr, CNS impair  
2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1  
ACGIH - LTE(8h): 50 ppm - Notes: Skin and eye irr  
ethanediol; ethylene glycol - CAS: 107-21-1  
EU - LTE(8h): 52 mg/m<sup>3</sup>, 20 ppm - STE: 104 mg/m<sup>3</sup>, 40 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)  
ACGIH - STE: C 100 mg/m<sup>3</sup> - Notes: A4 (H) - URT and eye irr  
ammonia, anhydrous - CAS: 7664-41-7  
EU - LTE(8h): 14 mg/m<sup>3</sup>, 20 ppm - STE: 36 mg/m<sup>3</sup>, 50 ppm - Notes: Bold-type: Indicative Occupational Exposure Limit Values [2,3] and Limit Values for Occupational Exposure [4] (for references see bibliography)  
ACGIH - LTE(8h): 25 ppm - STE: 35 ppm - Notes: Eye dam, URT irr
- DNEL Exposure Limit Values  
N.A.
- PNEC Exposure Limit Values  
N.A.
- 8.2. Exposure controls  
Eye protection:  
Use close fitting safety goggles, don't use eye lens.
- Protection for skin:  
Use clothing that provides comprehensive protection to the skin, e.g. cotton, rubber, PVC or viton.
- Protection for hands:  
Use protective gloves that provides comprehensive protection, e.g. P.V.C., neoprene or rubber.
- Respiratory protection:  
Use adequate protective respiratory equipment.
- Thermal Hazards:  
None
- Environmental exposure controls:  
None
- Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes:
Appearance and colour:	Liquido bianco	--	--
Odour:	caratteristico solvente	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	>37 ° C	--	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	>1	--	--
Relative density:	1,200Kg/l	--	--
Solubility in water:	insolubile	--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	N.A.	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

### 9.2. Other information

Properties	Value	Method:	Notes:
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

It may generate dangerous reactions (See subsections below)

### 10.2. Chemical stability

It may generate dangerous reactions (See subsections below)

### 10.3. Possibility of hazardous reactions

None

### 10.4. Conditions to avoid

Avoid accumulating electrostatic charge.

### 10.5. Incompatible materials

Avoid contact with combustible materials. The product could catch fire.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Toxicological information of the mixture:

N.A.

Toxicological information of the main substances found in the mixture:

Idrocarburi ,C9-C12,n-alcani,isolacani-ciclici,aromatici(2-25%) - CAS: 1174921-79-9

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat > 13.1 mg/l - Source: OCSE 403

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OCSE 401

Test: LD50 - Route: Skin - Species: Rabbit > 4 ml/kg - Source: OCSE 402

c) serious eye damage/irritation:

Test: Eye Irritant - Source: OCSE 405

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

a) acute toxicity:

Test: LC50 - Route: Inhalation - Species: Rat 8000 Ppm  
Test: LD50 - Route: Oral - Species: Rat > 2830 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg  
2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime - CAS: 96-29-7  
a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat 3000 mg/kg - Notes: Tossicità acuta  
Test: LC50 - Route: Inhalation - Species: Rat > 4.8 mg/l - Duration: 4h  
o-xylene - CAS: 1330-20-7  
LD50 (RAT) ORAL: 5000 MG/KG

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

## SECTION 12: Ecological information

### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

Idrocarburi ,C9-C12,n-alcani,isolacani-ciclici,aromatici(2-25%) - CAS: 1174921-79-9

#### a) Aquatic acute toxicity:

Endpoint: L6 - Species: Daphnia = 10-22 mg/l - Duration h: 48

Endpoint: L7 - Species: Algae = 1 mg/l - Duration h: 72

Endpoint: L6 - Species: Algae = 4.6-10 mg/l - Duration h: 72

Endpoint: L9 - Species: Daphnia = 0.097 mg/l - Duration h: 504

Endpoint: L10 - Species: Daphnia = 0.203 mg/l - Duration h: 504

2-methylpropan-1-ol; iso-butanol - CAS: 78-83-1

#### a) Aquatic acute toxicity:

Endpoint: EC50 - Species: Daphnia 100 mg/l - Duration h: 48

Endpoint: EC50 - Species: Algae 1799 mg/l - Duration h: 72

Endpoint: LC50 - Species: Fish 1430 mg/l - Duration h: 96

2-butanone oxime; ethyl methyl ketoxime; ethyl methyl ketone oxime - CAS: 96-29-7

#### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 48 mg/l - Duration h: 96

Endpoint: EC50 - Species: Daphnia = 750 mg/l - Duration h: 48

Endpoint: 4 - Species: Algae = 100 mg/l - Duration h: 72

### 12.2. Persistence and degradability

None

Idrocarburi ,C9-C12,n-alcani,isolacani-ciclici,aromatici(2-25%) - CAS: 1174921-79-9

Biodegradability: Not persistent and Biodegradable - Test: N.A. - Duration: N.A. - %: N.A. - Notes: N.A.

### 12.3. Bioaccumulative potential

N.A.

### 12.4. Mobility in soil

N.A.

### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

### 12.6. Other adverse effects

None

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Recover, if possible. Send to authorised disposal plants or for incineration under controlled conditions. In so doing, comply with the local and national regulations currently in force.

## SECTION 14: Transport information

- 14.1. UN number  
 ADR-UN Number: 1263  
 IATA-UN Number: 1263  
 IMDG-UN Number: 1263
- 14.2. UN proper shipping name  
 ADR-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)  
 IATA-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)  
 IMDG-Shipping Name: PAINT (including paint, lacquer, enamel, stain, shellac, varnish, polish, liquid filler and liquid lacquer base) or PAINT RELATED MATERIAL (including paint thinning and reducing compound)
- 14.3. Transport hazard class(es)  
 ADR-Class: 3  
 ADR - Hazard identification number: 30  
 IATA-Class: 3  
 IATA-Label: 3  
 IMDG-Class: 3
- 14.4. Packing group  
 ADR-Packing Group: III  
 IATA-Packing group: III  
 IMDG-Packing group: III
- 14.5. Environmental hazards  
 ADR-Environmental Pollutant: No  
 IMDG-Marine pollutant: No
- 14.6. Special precautions for user  
 Rail (RID): 3.III  
 ADR-Subsidiary risks: -  
 ADR-S.P.: 163 640E 650  
 ADR-Tunnel Restriction Code: (D/E)  
 IATA-Passenger Aircraft: 355  
 IATA-Subsidiary risks: -  
 IATA-Cargo Aircraft: 366  
 IATA-S.P.: A3 A72  
 IATA-ERG: 3L
- IMDG-EmS: F-E , S-E
- IMDG-Subsidiary risks: -  
 IMDG-Storage category: Category A  
 IMDG-Storage notes: -
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
 N.A.

## SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
 Dir. 98/24/EC (Risks related to chemical agents at work)  
 Dir. 2000/39/EC (Occupational exposure limit values)  
 Regulation (EC) n. 1907/2006 (REACH)  
 Regulation (EC) n. 1272/2008 (CLP)  
 Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013  
 Regulation (EU) 2015/830  
 Regulation (EU) n. 286/2011 (ATP 2 CLP)  
 Regulation (EU) n. 618/2012 (ATP 3 CLP)  
 Regulation (EU) n. 487/2013 (ATP 4 CLP)  
 Regulation (EU) n. 944/2013 (ATP 5 CLP)  
 Regulation (EU) n. 605/2014 (ATP 6 CLP)
- Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:  
 Restrictions related to the product:  
 Restriction 3  
 Restriction 40  
 Restrictions related to the substances contained:  
 No restriction.
- Volatile CMR substances = 0.00 %

Halogenated VOCs which are assigned the risk phrase R40 = 0.00 %

Organic Carbon - C = 0.00

Where applicable, refer to the following regulatory provisions :

Directive 82/501/EEC ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directives 82/501/EC(Seveso), 96/82/EC(Seveso II):

N.A.

15.2. Chemical safety assessment

No

## SECTION 16: Other information

Text of phrases referred to under heading 3:

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

H315 Causes skin irritation.

H312 Harmful in contact with skin.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H318 Causes serious eye damage.

H351 Suspected of causing cancer.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H319 Causes serious eye irritation.

H361 Suspected of damaging fertility or the unborn child in contact with skin and if swallowed.

H410 Very toxic to aquatic life with long lasting effects.

H302 Harmful if swallowed.

H221 Flammable gas.

H280 Contains gas under pressure; may explode if heated.

H314 Causes severe skin burns and eye damage.

H331 Toxic if inhaled.

This safety data sheet has been completely updated in compliance to Regulation 453/2010/EU.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

Insert further consulted bibliography

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.



PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.